



COLLINS

COLLINS CONSTRUCTION MATERIALS PTY LIMITED

MATERIAL SAFETY DATA SHEET

Collins Native Mix

Hazardous ("Xn" Harmful, "Xi Irritant, "T" Possible Carcinogen by inhalation - Category 2)
according to the *Approved Criteria for Classifying Hazardous Substances*
[NOHSC:1008(2004)]

IMPORTANT NOTICE: This Material Safety Data Sheet (MSDS) is issued by Collins Construction Materials Pty Limited in accordance with National Work Health and Safety Commission guidelines. The information contained in this document must not be added to, deleted or altered. Collins Construction Materials Pty Limited will issue a new MSDS when there is a change on the product specifications and/or with the National Work Health & Safety Commission guidelines/regulation. Collins Construction Materials Pty Limited will not accept any responsibility for any changes made to its MSDS in content by any other person or organisation.

Section 1 - Identification of the Material and Supplier

Product (Material) Name: Native Mix

Other Name: Not Applicable

Supplier Name: Collins Construction Materials Pty Limited

Supplier Address: 214 Macarthur Road, Spring Farm NSW 2570

Supplier Telephone: (02) 4658 1666

Supplier Fax: (02) 4658 1846

Supplier Emergency Tel (24 hours): 0413 801 154

Emergency Services Tel (24 hours): 000

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 1 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS

COLLINS CONSTRUCTION MATERIALS PTY LIMITED

Section 2 - Hazards Identification

Hazard Classification: **HAZARDOUS SUBSTANCE. NON DANGEROUS GOODS.** Due to the small silica particles in this product it is classified as a hazardous substance according to the Approved Criteria for Classifying Hazardous Substances [NOHSC:1008)2004)]

Risk Phases:

- R42** May cause sensitisation by inhalation
- R43** May cause sensitisation by skin contact
- R49** May cause cancer by inhalation

"Xn" Harmful
"Xi" Irritant
"T" Possible Carcinogen inhalation (Category 2).

Section 3 - Composition/Information on Ingredients

Common Names/Synonyms: Compost, Ash and soil

CAS Number: Not applicable

Origin: Mixture of imported composted material, ash and naturally extracted materials.

Recommended Use: Commonly used for Australian native plants and other plants required for drainage soils.

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 2 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



Section 4 - First Aid Measures

Facilities should be available where this product is used to carry out first aid procedures.

Description of Necessary First Aid Measures

Ingestion: Swallowing this product may cause immediate or delayed abdominal discomfort and potentially increase the risk of gastro-intestinal infections.

The patient should be given water to drink and medical attention should be sought if any abdominal symptoms occur. Vomiting should not be induced, but if vomiting occurs, the patient should be leant forward or placed on their side to maintain an open airway.

Eye: In the event that this material or the dust comes into contact with the eyes it may have an immediate or delayed effect resulting in redness, watering and/or infection.

Eyes should be immediately and thoroughly flushed with lukewarm water for as long as necessary to alleviate the problem (or for at least 15 minutes). Ensure complete irrigation of the eye by keeping eyelids apart and away from the eye and moving the eyelids by occasionally lifting the upper and lower lids. Removal of contact lenses after an eye injury should only be conducted by skilled personnel. Professional medical assistance should be sought if symptoms persist.

Skin: Skin contact with this product and/or their ducts may lead to immediate or delayed skin irritations and in susceptible people skin sensitisation, dermatitis and/or skin infection.

The affected areas should be washed thoroughly with mild soap and lukewarm water as quickly as possible.

Inhalation: Inhalation of dust from this product may have an immediate or delayed effect to irritate, inflame or sensitive the nose, throat and lungs and exacerbate pre-existing conditions such as asthma and bronchitis. The repeated inhalation of dust from these products may lead to asthma, bronchitis, cancer, pneumonia

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins			Page 3 of 10
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS CONSTRUCTION MATERIALS PTY LIMITED

or other pneumonia-like illnesses. Children, pregnant women, the elderly, people with pre-existing conditions or the immuno-compromised may at a particular risk from these illnesses if exposed to this product.

If an irritation occurs, the affected parties should be moved (or move themselves) away from the product or its dusts into a source of fresh air. The patient should be laid down, kept warm and be rested. Prostheses such as false teeth, which may block the airways should be removed where possible prior to initiating first aid procedures. Professional medical attention should be sought if symptoms persist.

Specific Medical Attention and Treatment

Needle stick injury's should be treated in the following manner:

1. PPE handling material with riggers gloves or better section 8
2. Action to take
 - a. Wash the wound with soap and water or alcohol based wipes
 - b. go straight to doctor or hospital emergency
 - c. give details information and the instrument that caused the injury in a sealed container if possible.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media: Not relevant (Not flammable)

Hazards from Combustion Products: Not relevant (Not flammable)

Precautions for Fire Fighters & Special Protective Equipment: Not relevant (Not flammable)

Section 6 - Accidental Release Measures

Emergency Procedures

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins			Page 4 of 10
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS CONSTRUCTION MATERIALS PTY LIMITED

In the event of a spill or release of the product from a transport vehicle or storage area:

1. Advise the Roads & Maritime Services (if a spill occurs from a transport vehicle) 132 701
2. Advise the Department of Environment & Conservation (DEC) on the pollution line and complete any necessary reports as advised. 131 555
3. Advise the product supplier emergency contact 0413 801 154

Methods and Materials for Containment and Clean Up Procedures

In the event of a spill or release of the product from a transport vehicle or storage area in order to contain and clean up:

- Secure the site by:
 - covering the material with a sheet/tarpaulin secured to the ground in order to protect against dust emissions and gravitational flows into waterways.
 - bunding the area and cover drains to protect against over ground run off in waterways, surrounding land and drainage systems.
- Clean up the spill immediately once the site is secured. Avoid generating dust.
- Collect the material (using a vacuum system if required), load, transport and store all the material released for use as planned or dispose of safely on a solid waste suitable landfill.
- Check the surrounding area to ensure all material has been captured. Collect all material if possible or seek Department of Environment & Conservation (DEC) advice if this has not been possible.

Section 7 - Handling and Storage

When handling this material that workers stay away from equipment that is moving and/or processing material and avoid coming into contact with the product by wearing:

- A suitable respiratory protective device conforming with AS/NZS 1715:1994- Selection, use and maintenance of respiratory protective devices. A Class P1

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 5 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS CONSTRUCTION MATERIALS PTY LIMITED

Particulate Respirator is typically most appropriate in dusty conditions with suitable PPE.

- Suitable eye protection conforming with AS/NZS 1336: 1997 - Recommended practices for protection. Low impact goggles with indirect ventilation (HT or CT with C, D optional) are typically most appropriate.

Additional handling procedures should include:

- Limit exposure to the product if dusty
- Wash any areas of the body that the product may have come into contact after exposure.
- Launder protective work clothes prior to re-use.
- Check the atmosphere regularly against the relevant exposure standards (Section 8)
- Regularly vacuum enclosed areas where the product is used or install another a dust extraction system.

When handling this material ensure the environment is protected from releases by not moving the material during adverse weather conditions such as wind and precipitation, bunding the handling area and providing wind breaks.

Conditions for Safe Storage

When storing this material:

- Protect stockpiles from wind and other adverse weather with a sheet/tarpaulin or wind break secured to the ground.
- Bund the storage area.

Section 8 - Exposure Control/Personal Protection

National Exposure Standards

No specific exposure standards have been allocated for Ferrous Alumina Silicate ($\text{Fe}_3\text{AlSiO}_4$). However due to the silica dust in the product, concentration for monitoring exposure are provided by Table 1 in Section 6.16 of the *Approved Criteria for Classifying Hazardous Substances [HOHSC:1008(2004)]* and a number of standards are applicable as listed below:

- **Total Inhalable Dust**
10mg/m³ (National Occupational Health & Safety Commission 2012)

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins			Page 6 of 10
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS CONSTRUCTION MATERIALS PTY LIMITED

- **Total Respirable Dust**
2mg/m³ (American Conference of Governmental Occupational Hygienists, 1986)
- **Respirable Crystalline Silica**
0.1mg/m³ (National Occupational Health & Safety Commission, 2004).

Biological Limit Values:	No Biological Limit Allocated
Engineering Controls:	Use only in well ventilated areas.
Personal Protection Equipment: full	Breathing masks (respirators), riggers gloves, length overalls, enclosed boots.

Section 9 - Physical and Chemical Properties

Appearance:	A light coloured material of fine particle size
Odour:	No odour
pH:	6 - >8.5
Electrical Conductivity:	less than 0.35 dS/m
Vapour Pressure:	Not relevant
Vapour Density:	Not relevant
Boiling Point/Range:	Not relevant
Freezing/Melting Point:	Not relevant
Solubility:	Not soluble
Specific Gravity or Density:	8 > 1 cubic tonnes per cubic metre (t/m ³)
Flashpoint:	Not relevant
Information for Flammable Materials:	Not Flammable

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 7 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



Section 10 - Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: None

Incompatible Materials: None

Hazardous Decomposition Products: None

Hazardous Reactions: None

Section 11 - Toxicological Information

Acute Healthy Effects

Ingestion: Ingestion is unlikely through normal use. However, swallowing any amount of this product may cause immediate or delayed abdominal discomfort and potentially increase the risk of gastro-intestinal infections.

Eye: In the event that any dose of this material or the dust comes into contact with the eyes it may have an immediate or delayed irritating effect resulting in redness and watering or an infection.

Skin: Any level of skin contact with this product and/or their dusts may lead to immediate or delayed skin irritations and in susceptible people skin sensitisation, dermatitis or skin infection.

Inhalation: Inhalation of any amount of dust from this product may have an immediate or delayed effect to irritate, inflame or sensitise the nose, throat and lungs, and exacerbate pre-existing conditions such as asthma and bronchitis. Prolonged inhalation of dust can cause cancer or pneumoconiosis (or silicosis), a disease that causes scarring or hardening (nodular fibrotic changes) of lung tissue.

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 8 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS

COLLINS CONSTRUCTION MATERIALS PTY LIMITED

Chronic Health Effects

The repeated inhalation of dust from these products may lead to respiratory irritation, inflammation or sensitisation and illnesses such as asthma, bronchitis, cancer, pneumonia or other pneumonia-like illnesses. Children, pregnant women, the elderly, people with pre-existing conditions or the immuno-compromised may be at a particular risk from these illnesses if exposed to this product. It is not recommended to repeatedly swallow this material or repeatedly allow it to come into contact with the eyes. All people who come into contact with this product should safeguard themselves from tetanus.

Section 12 - Ecological Information

- Ecotoxicity:** **R53** May cause long-term adverse effects in the aquatic environment.
- R58** May cause long-term adverse effects in the environment.
- Persistence/
Degradability:** Not harmful persistent, no harmful degrading.
- Mobility:** Only mobile in significant water and wind.

Section 13 - Disposal Considerations

- Disposal Methods:** Solid waste suitable landfill
- Special Precautions for Landfill or Incineration:** Not relevant

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins			Page 9 of 10
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			



COLLINS

COLLINS CONSTRUCTION MATERIALS PTY LIMITED

Section 14 - Transport Information

UN Number: None

Proper Shipping Name: None

Class and Subsidiary Risk(s): None

Packing Group: None

Special Precautions for User: Trucks to use a tarpaulin to cover the load.

Section 15 - Other Information

Date of Issue: 1 May 2013

Date of Revision: 1 May 2018

Specific of Query Contact:

Name: Darren Hunt

Position: The Work Health & Safety Representative

Query Telephone: 0413 801 154

Weighbridge: (02) 4658 1666

END OF MSDS

Last Modified: 05/ 2013	Version: 1	Doc No:	Document Name: MSDS Native Mix
Approved by : Matthew Collins		Page 10 of 10	
PRINTED COPY UNCONTROLLED			
© Copyright Collins Construction Materials Pty Limited ABN 61 156 660 525			