28 February 2019



Our Ref: 201019

Mr M Collins Collins Construction Materials Pty Ltd 214 MacArthur Road Elderslie NSW 2570

Dear Matt,

#### Re: Environmental Monitoring - Spring Farm: Report 2019-2

This is to confirm that groundwater sampling and dust monitoring at Spring Farm (see Appendix 1 for sample locations) has been carried out with the results summarised in Tables 1 and 2 respectively below.

#### (a) Groundwater Monitoring

TABLE 1: SUMMARY OF GROUNDWATER MONITORING RESULTS.									
ANALYTE VALUE TARGET DATE TIME TEMP									
EC (uS/cm)	264 (Non-Saline)	< 800 uS/cm							
pН	5.72 (Moderately acidic)	4 – 6.50	4-2-2019	8.00 am	22ºC				
Depth to Water Table (m) <sup>1</sup>	11.50	> 10 m							

**Notes:** 1. This value represents the depth to groundwater from the TOP OF THE STAND PIPE (670 mm above ground level); 2. Refer to Appendix 2 for laboratory analysis results and monthly summary data 3 Refer to Appendix 3 for quality control documentation.

The results indicate that groundwater is:

- Non-saline and is well below the nominated target of < 800uS/cm;</li>
- Moderately acidic and falling within the nominated pH range of 4 6.50;
- At the limit of the target depth > 10 m.

#### (b) Dust Monitoring

TABLE 2: SUMMARY OF DUST DEPOSITION MONITORING RESULTS.										
SAMPLING PERIOD	LOCATION	TOTAL INSOLUBLE MATTER <sup>1</sup> (G/M2/MONTH)	Ash or Mineral Content (g/m2/month)	COMMENT	EMP targets (Ash or Mineral Content)					
	1	1.6	NT	Pass						
JANUARY	2	3.5	NT	Pass	≤ 4g / m2 per month					
2019	3	4.7	NT	Fail	per monu					

Notes: 1.Refer to Appendix 1 for monitoring locations. 2. Refer to Appendix 2 for laboratory analysis results and monthly summary data. Refer to Appendix 3 for quality control documentation.

A slight exceedance was recorded for monitoring Station 3 whilst Stations 1 and 2 values met the EMP target level.

Yours faithfully,

Mart Rampe BSc (Applied Geology)
Principal Consultant

All Correspondence to: PO Box 427 Narellan NSW 2567 Unit 4, 20 Somerset Avenue NARELLAN NSW 2567 www.harvestscientific.com.au Email: narellan@harvestscientific.com.au
Tel: 02 4647 6177 • Fax: 02 4647 7332

# **APPENDIX 1: Collins Spring Farm Monitoring Locations**

MS 1: Dust MS 2: Dust MS 3: Dust

**GW-1: Groundwater** 



APPENDIX 2: Laboratory Analytical Results and monthly summa	ry data

ENVIRONMENTAL MONITORING: COLLINS CONSTRUCTION MATERIAL PTY LTD - SPRING FARM



#### **CERTIFICATE OF ANALYSIS**

Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Contact : MR MART RAMPE

Address : PO BOX 427

NARELLAN NSW, AUSTRALIA 2567

Telephone : +61 02 4647 6177

Project : COLLINS SPRING FARM

Order number : 2019-2

C-O-C number : ---Sampler : MR
Site : ----

Quote number : EN/222

No. of samples received : 3

No. of samples analysed : 3

Page : 1 of 2

Laboratory : Environmental Division Newcastle

Contact :

Address : 5/585 Maitland Road Mayfield West NSW Australia 2304

Telephone : +61 2 4014 2500

Date Samples Received : 05-Feb-2019 17:45

Date Analysis Commenced : 06-Feb-2019

Issue Date : 12-Feb-2019 18:26



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with Quality Review and Sample Receipt Notification.

#### Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Dianne Blane Laboratory Coordinator (2IC) Newcastle - Inorganics, Mayfield West, NSW

Page : 2 of 2 Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM

#### General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

- ^ = This result is computed from individual analyte detections at or above the level of reporting
- ø = ALS is not NATA accredited for these tests.
- ~ = Indicates an estimated value.
- Analysis as per AS3580.10.1-2016. Samples passed through a 1mm sieve prior to analysis. NATA accreditation does not apply for results reported in g/m².mth as sampling data was provided by the client.
- Sample exposure period is 24 days which is outside the typical exposure period of 30 +/- 2 days as per AS3580.10.1.

#### Analytical Results

Sub-Matrix: <b>DEPOSITIONAL DUST</b> (Matrix: <b>AIR</b> )	Client sample ID		COLLINS 1 11/01/19 - 04/02/19	COLLINS 2 11/01/19 - 04/02/19	COLLINS 3 11/01/19 - 04/02/19	 	
	Cli	ient sampli	ng date / time	04-Feb-2019 11:00	04-Feb-2019 11:00	04-Feb-2019 17:43	 
Compound	CAS Number LOR Unit		EN1900808-001	EN1900808-002	EN1900808-003	 	
				Result	Result	Result	 
EA120: Ash Content							
Ash Content		0.1	g/m².month			4.0	 
Ash Content (mg)		1	mg			57	 
EA141: Total Insoluble Matter							
Total Insoluble Matter		0.1	g/m².month	1.6	3.5	4.7	 
Total Insoluble Matter (mg)		1	mg	22	49	66	 



Period	TIM (g/m2/month)		onth)	Notes	Controls Implemented			
	MS 1	MS 2	MS 3					
Feb-13	1.2	1.5	0.5	Introduction of Station 3				
Mar-13	0.6		2					
Apr-13	1.6		3.1*	*TIM exceedance	*Measured Ash Content			
May-13	0.4	0.8	1.8					
Jun-13	0.7	1.3	1.7					
Jul-13	0.4	0.5	1.3 0.4					
Aug-13 Sep-13	0.4		0.4					
Oct-13	0.7	1.2	1.1					
Nov-13	0.1	0.3	0.1					
Dec-13	1.7	1.1	1.2					
Jan-14	0.7	0.9	1					
Feb-14	0.8	1.9	0.7					
Mar-14	0.7	1.4	1.8					
Apr-14	0.4		0.6					
May-14	1.2		1.2	Cheyne Hudson takes over sampling and reporting	Mesh screens inserted to filter organic content			
Jun-14	0.1		0.1					
Jul-14	0.4		0.8 **	*[				
Aug-14	2	2*		*Funnel in jug smashed **Jug smashed.				
Sep-14	2.1	0.6	1.5					
Oct-14	1.8	0.9 2.8	1.6 6.2*	*Cite clean-up and may an adjacent rental proced-				
Nov-14 Dec-14	1.5 2.2	2.8	1.6	*Site clean-up and mow on adjacent rental property				
Jan-15	1.2	1.2	2					
Feb-15	1.7	0.9	2.3					
Mar-15	2.9	3.3	3.6					
Apr-15	2.9 6*	1.6	4.4	*New earthworks noted 50 metres from M1	*Monitor results May-15 due to new E1 extraction			
May-15	1.5		0.9	New earthworks noted 30 metres nominal	Monitor results May-13 due to new El extraction			
Jun-15	1.6		2.0					
Jul-15	1.9	0.8	1.5					
Aug-15	4.2*	1.1	2.5	*Expanded quarry area to within 20 m of M1.	*Relocation of Monitoring Sites 1 and 2 (September)			
Sep-15	1.7	0.9	6.1*	*Expansion of nearby Spring Farm urban	*Regular inspection monitor urban development activity			
Oct-15	3.9	4	6.4*	*Hot windy weather and nearby grass mowing	*Dust suppression irrigation			
Nov-15	1.7	0.5	2.4	, , , , , , , , , , , , , , , , , , , ,				
Dec-15	3.5	2.4	5.3*	development	*Regular inspection monitor urban development activity			
Jan-16	2	1	4.7*	*Expansion of nearby Spring Farm urban	*Regular inspection monitor urban development activity			
Feb-16	1.5	1.1	1.9	p	.,			
Mar-16	3.3	2.5	2.5					
Apr-16	1.2		2					
May-16	0.9	1.5	1.6					
Jun-16	2.7	3.6	3.2					
Jul-16	0.9	0.8	4					
Aug-16	0.5	3.3	0.8					
Sep-16	1.0	2.3	1.6					
Oct-16	1.2	0.7	1.8					
Nov-16	1.0	0.8	2.8					
Dec-16	1.6	2.6	11*	*Springs Road widening and very hot dry weather				
Jan-17	1.3	1.3	2.9					
Feb-17	1.0	0.9	2.1					
Mar-17	2.7	1.5	1.8					
Apr-17	0.6	0.4	2.9					
May-17	0.7	1	1.8					
Jun-17	1.2	1	1.3					
Jul-17	0.8		1.5					
Aug-17	0.3	1	2.2		<u> </u>			
Set - 17	1.0	1.6	4.3	High vegetable (leaves)and organic (bugs) content in a	II samples			
Oct-17	1.7		2.2		<u> </u>			
Nov-17	0.9	1.5	4.6	High vegetable (leaves) and organic (bugs) content in a	II samples			
Dec-17	0.6	1.2	2.3					
Jan-18	1.3	2.0	2.8	March at and documents				
Feb-18	0.5	1.9	5.6	Very hot and dry month				
Mar-18	0.6	0.7	7.2	Very hot and dry month and at times windy				
Apr-18	6.7	1.1	2.6	MS-1 sample polluted - bird droppings?				
May-18	0.4		2.5	MC 4 assessed bishburgett to describe the second				
Jun-18	0.5	0.5	34.1	MS-1 sample highly polluted - anomalous result				
Jul-18	0.4		0.7					
Aug-18	0.6		0.7					
Sep-18	1.0		1.5					
Oct-18 Nov-18	0.7	1.2	1.4 1.8					
Dec-18		1						
	2.4		2.0	Vany hat and dry month and at time a mind.				
Jan-19	1.6	3.5	4.7	Very hot and dry month and at times windy				



#### **CERTIFICATE OF ANALYSIS**

**Work Order** : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Contact : MR MART RAMPE

Address : PO BOX 427

NARELLAN NSW. AUSTRALIA 2567

Telephone : +61 02 4647 6177 Project : Collins Spring Farm

Order number : 2019-2

C-O-C number

Sampler · MART RAMPE

Site

Quote number : EN/222

No. of samples received : 1 No. of samples analysed : 1 Page : 1 of 2

Laboratory : Environmental Division Sydney

Contact : Customer Services ES

Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

Telephone : +61-2-8784 8555 **Date Samples Received** : 04-Feb-2019 16:30

**Date Analysis Commenced** : 04-Feb-2019

Issue Date : 05-Feb-2019 11:12



ISO/IEC 17025 - Testing

This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full.

This Certificate of Analysis contains the following information:

- General Comments
- Analytical Results

Additional information pertinent to this report will be found in the following separate attachments: Quality Control Report, QA/QC Compliance Assessment to assist with **Quality Review and Sample Receipt Notification.** 

#### Signatories

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Ankit Joshi Inorganic Chemist Sydney Inorganics, Smithfield, NSW Page : 2 of 2 Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm

# ALS

#### **General Comments**

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis.

Where the LOR of a reported result differs from standard LOR, this may be due to high moisture content, insufficient sample (reduced weight employed) or matrix interference.

When sampling time information is not provided by the client, sampling dates are shown without a time component. In these instances, the time component has been assumed by the laboratory for processing purposes.

Where a result is required to meet compliance limits the associated uncertainty must be considered. Refer to the ALS Contact for details.

Key: CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

- ^ = This result is computed from individual analyte detections at or above the level of reporting
- ø = ALS is not NATA accredited for these tests.
- ~ = Indicates an estimated value.

#### Analytical Results

Sub-Matrix: WATER (Matrix: WATER)	Client sample ID			COLLINS GW-1	 	 
	ient sampli	ng date / time	04-Feb-2019 11:00	 	 	
Compound	CAS Number LOR Unit		ES1903377-001	 	 	
				Result	 	 
EA005P: pH by PC Titrator						
pH Value		0.01	pH Unit	5.72	 	 
EA010P: Conductivity by PC Titrator						
Electrical Conductivity @ 25°C		1	μS/cm	264	 	 

GROUNDW	ATER MONITO	RING STATION	I GW-1: COLLIN	S SITE		
Date	Time	Temp. (°C)	EC (uS/cm)	рН	Depth to Water Table (m)	Comments
10-03-09	15:30	N/A	528	< 6.2	from top of stand pipe 11.59	pH was measured using a QUIKCHEK pH test strip.
01-04-09	11:00	N/A	533	< 6.2	11.50	pH was measured using a Eutech pH 5+ meter
01-05-09	10:35	N/A	533	< 6.2	11.50	
01-06-09	10:25	17.3	541	4.79	11.50	
24-06-09 31-07-09	10:20 9:05	17.3	542 598	4.53 4.98	11.50 11.59	
31-08-09	9:07	17.6	610	4.81	11.60	
30-09-09	9:45	18	619	4.71	11.59	
30-10-09	9:45	18.5	621	4.75	11.47	
27-11-09	8:00	19	~	4.73	11.47	
04-01-10	9:50	18.5	634	4.73	11.51	
02-02-10	9:45	18.7	641	4.78	11.52	
01-03-10	9:50	18.1	635	4.67	11.56	
31-03-10	9:15	18.2	639	4.74	11.56	
30-04-10	9:15	17.8	640	4.76	11.56	
01-06-10	10:40	18.1	640	4.66	11.56	
30-06-10	9:30	16.4	614	5.17	11.56	
02-08-10	10:40	17.4	639	4.64	11.56	
01-09-10	9:30	18.6	641	4.82	11.56	
05-10-10	15:50	19.3	651	4.61	11.56	
05-11-10	15:30	18.5	657	5.12	11.36	
07-12-10	9:50	19	670	5.09	11.32	
23-12-10	12:30	19.5	952	5.12	11.32	
01-02-11	12:00	20.3	657	5.17	11.39	
01-04-11	11:00	18.7	778	5.01	11.39	
29-04-11	11:30	18.3	745	5.12	11.39	
30-05-11	10:30	17	777	5.64	11.39	
01-07-11 29-07-11	16:30 15:30	16.5 18.5	763 775	5.27	11.39 11.29	
01-09-11	15:30	18.8	851	4.64	11.29	
04-10-11	13:00	18.4	847	4.66	11.29	
28-10-11	15:30	19.5	846	4.48	11.29	
01-12-11	8:30	17.9	896	4.51	11.35	
23-12-11 01-02-12	9:45 16:15	18.8 18.9	793 782	4.49	11.35 11.35	
28-02-12	8:30	18.7	806	4.42	11.35	
30-03-12 30-04-12	15:30 14:30	19.7 18.9	775 772	4.52 4.59	10.77	
31-05-12	12:30	19	744	4.55	10.78	
08-07-12	10:30	17.5	784	4.46	10.90	
02-08-12	8:00	13.2	769	4.53	11.05	
03-09-12	15:30	19.3	759	4.66	11.20	
29-09-12	15:00	19.2	799	4.67	11.47	
01-11-12	15:00	19.8	786	4.67	11.30	
03-12-12	13:00	19.1	769	4.81	11.69	
28-12-12	14:30	19.1	767	4.69	11.69	
31-01-13	11:30	19.2	789	4.82	11.40	Prolonged period of heavy rain.
04-03-13	9:30	19.1	757	4.78	11.09	
03-04-13	N/A	N/A	756	5.24	11.21	New site personnel (Simon Winter).  Commenced laboratory analysis of pH and EC
03-05-13	9:30	N/A	620	4.40	11.17	
03-06-13 03-07-13	15:05 15:00	N/A N/A	670 690	4.80	11.20 10.85	Commenced laboratory analysis of private 20
02-08-13 03-09-13	15:00 14:30	N/A 23	700 700	5.10 4.40	10.80 10.80 11.05	
03-10-13	12:05	16	680	4.40	11.15	
04-11-13 03-12-13	11:25 10:30	18 23	640 690	4.80	11.35 11.28	
09-01-14	14:00	19	670	4.80	11.49	
04-02-14	9:45	24	680	4.60	11.49	
07-03-14	9:55	21	545	4.60	11.50	
04-04-14	10:05	20	700	4.90	11.37	
06-05-14	10:00	16	690	4.80	11.37	
03-06-14	12:15	18	652	5.26	11.47	
02-07-14	11:45	17	688	5.54	11.55	New site personnel (Cheyne Hudson).
06-08-14	11:45	20	648	5.94	11.60	
09-09-14	11:45	21	636	5.30	11.30	
08-10-14	11:30	20	628	5.40	11.45	
13-11-14	11:30	22	609	5.74	11.50	
03-12-14	12:00	30	598	5.84	11.50	
09-01-15	12:00	30	601	5.68	11.45	
11-02-15	11:45	28	588	5.43	11.45	
10-03-15	12:00	22	581	5.79	11.45	
08-04-15	11:00	20	573	5.13	11.45	
07-05-15 10-06-15	11.00	20 20 15	527 507	5.26 5.28	11.20	Sampling undertaken by M Rampe
06-07-15	10.00	10	500	4.96	11.20 11.20	
07-08-15	10:00	12	480	5.58	11.45	
03-09-15	9:00	11	417	5.75	11.25	
08-10-15	9:00	16	423	5.15	11.50	
06-11-15	9:00	22	456	5.26	11.45	
07-12-15	10:00	23	434	5.25	11.50	
04-01-16	11:00	20	409	5.00	11.50	
05-02-16	10:45	22	410	5.61	11.60	
03-03-16	9:00	23	399	5.23	11.60	
06-04-16	9:00	23	359	5.03	11.40	
05-05-16	12:30	22	363	5.77	11.50	
03-06-16	2:00	18	377	5.47	11.60	
04-07-16	12.30	13	372	5.32	10.70	
03-08-16 05-09-16	10.00	12 12	261 250	6.84 5.62	10.70 10.40	
01-10-16 01-11-16	10.00 10.00 8.00	12	252 296	6.16 5.93	10.50 10.70	
01-12-16	8.00	12	352	5.63	10.70	
06-01-17	11.00	21	363	5.45	10.70	
03-02-17	8.30	22	334	5.53	11.10	
03-03-17	8.30	23	361	5.25	11.10	
04-04-17	8.30	16	392	5.46	10.80	
01-05-17	10.30	16	294	6.09	10.70	
01-06-17	8.00	8	373	5.12	11.00	
03-07-17	8.00	2	356	5.63	10.90	
01-08-17	9.00	12	346	6.00	11.00	
04-09-17	9.00	12	352	5.63	11.00	
10-10-17	8.00	16	349	5.57	11.10	
06-11-17	9.00	16	326	5.06	11.00	
05-12-17	9.00	18	304	5.42	11.20	
11-01-18 07-02-18	9.00	22 25	305 303	5.72 4.94	11.10	
07-03-18 06-04-18	9.00	20 22	302 318	4.86	11.40 11.40	
03-05-18	10.00	12	307	5.37	11.50	
05-06-18 06-07-18	10.00	14 20	304 306	5.60 5.61	11.60 11.50	
02-08-18 03-09-18	9.00	15 6	303 311	5.95 5.57	11.50 11.60	
03-10-18	10.00	14	338	6.24	11.60	
05-11-18	10.00	20	324	6.25	11.60	
03-12-18	8.30	20	324	6.09	11.60	
11-01-19	10.00	23	291	6.07	11.50	
04-02-19	8.00	22	264	5.72	11.50	

APPENDIX 3: Laboratory Quality Control Documentation								



#### **QUALITY CONTROL REPORT**

Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Contact : MR MART RAMPE

Address : PO BOX 427

NARELLAN NSW, AUSTRALIA 2567

Telephone : +61 02 4647 6177

Project : COLLINS SPRING FARM

Order number : 2019-2

C-O-C number : ----

Sampler : MR Site : ----

Quote number : EN/222

No. of samples received : 3
No. of samples analysed : 3

Page : 1 of 3

Laboratory : Environmental Division Newcastle

Contact

Address : 5/585 Maitland Road Mayfield West NSW Australia 2304

Telephone : +61 2 4014 2500
Date Samples Received : 05-Feb-2019
Date Analysis Commenced : 06-Feb-2019

Issue Date : 12-Feb-2019



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full. This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

#### **Signatories**

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Dianne Blane Laboratory Coordinator (2IC) Newcastle - Inorganics, Mayfield West, NSW

Page : 2 of 3 Work Order : EN1900808

Client · HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM



#### General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis. Where the LOR of a reported result differs from standard LOR, this may be due to high

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

# = Indicates failed QC

#### Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR: No Limit; Result between 10 and 20 times LOR: 0% - 50%; Result > 20 times LOR: 0% - 20%.

• No Laboratory Duplicate (DUP) Results are required to be reported.

Page : 3 of 3 Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM



#### Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Spike (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

• No Method Blank (MB) or Laboratory Control Spike (LCS) Results are required to be reported.

#### Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

• No Matrix Spike (MS) or Matrix Spike Duplicate (MSD) Results are required to be reported.



# QA/QC Compliance Assessment to assist with Quality Review

Work Order : **EN1900808** Page : 1 of 4

Client : HARVEST SCIENTIFIC SERVICES Laboratory : Environmental Division Newcastle

 Contact
 : MR MART RAMPE
 Telephone
 : +61 2 4014 2500

 Project
 : COLLINS SPRING FARM
 Date Samples Received
 : 05-Feb-2019

 Site
 : --- Issue Date
 : 12-Feb-2019

Sampler : MR No. of samples received : 3
Order number : 2019-2 No. of samples analysed : 3

This report is automatically generated by the ALS LIMS through interpretation of the ALS Quality Control Report and several Quality Assurance parameters measured by ALS. This automated reporting highlights any non-conformances, facilitates faster and more accurate data validation and is designed to assist internal expert and external Auditor review. Many components of this report contribute to the overall DQO assessment and reporting for guideline compliance.

Brief method summaries and references are also provided to assist in traceability.

## **Summary of Outliers**

#### **Outliers: Quality Control Samples**

This report highlights outliers flagged in the Quality Control (QC) Report.

- NO Method Blank value outliers occur.
- NO Duplicate outliers occur.
- NO Laboratory Control outliers occur.
- NO Matrix Spike outliers occur.
- For all regular sample matrices, NO surrogate recovery outliers occur.

#### **Outliers: Analysis Holding Time Compliance**

NO Analysis Holding Time Outliers exist.

#### **Outliers : Frequency of Quality Control Samples**

• NO Quality Control Sample Frequency Outliers exist.

Page : 2 of 4 Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM



#### **Analysis Holding Time Compliance**

If samples are identified below as having been analysed or extracted outside of recommended holding times, this should be taken into consideration when interpreting results.

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times (referencing USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive or Vinyl Chloride and Styrene are not key analytes of interest/concern.

Matrix: AIR

Evaluation: **x** = Holding time breach : ✓ = Within holding time.

Matrix. All					Lvaldation	Holding time	bicacii, within	ir noiding til	
Method			Ex	traction / Preparation		Analysis			
Container / Client Sample ID(s)			Date extracted	Due for extraction	Evaluation	Date analysed	Due for analysis	Evaluation	
EA120: Ash Content									
Dust Gauge - Copper Sulfate (EA120) COLLINS 3 - 11/01/19 - 04/02/19		04-Feb-2019				12-Feb-2019	03-Aug-2019	<b>✓</b>	
EA141: Total Insoluble Matter									
Dust Gauge - Copper Sulfate (EA141)  COLLINS 1 - 11/01/19 - 04/02/19,  COLLINS 3 - 11/01/19 - 04/02/19	COLLINS 2 - 11/01/19 - 04/02/19,	04-Feb-2019				06-Feb-2019	03-Aug-2019	✓	

Page : 3 of 4
Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM



# **Quality Control Parameter Frequency Compliance**

No Quality Control data available for this section.

Page : 4 of 4 Work Order : EN1900808

Client : HARVEST SCIENTIFIC SERVICES

Project : COLLINS SPRING FARM



#### **Brief Method Summaries**

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
Ash Content (AC)	EA120	AIR	In house: Referenced to AS 3580.10.1. A gravimetric procedure reporting Ash content in deposited dust.
Total Insoluble Matter (TIM)	EA141	AIR	In house: Referenced to AS 3580.10.1. A gravimetric procedure reporting Total Insoluble solids in deposited dust.



#### **QUALITY CONTROL REPORT**

Work Order : **ES1903377** 

: HARVEST SCIENTIFIC SERVICES

Contact : MR MART RAMPE

Address : PO BOX 427

NARELLAN NSW, AUSTRALIA 2567

Telephone : +61 02 4647 6177
Project : Collins Spring Farm

Order number : 2019-2

C-O-C number ; ---

Sampler : MART RAMPE

Site · ----

Quote number : EN/222

No. of samples received : 1
No. of samples analysed : 1

Page : 1 of 3

Laboratory : Environmental Division Sydney

: 04-Feb-2019

Contact : Customer Services ES

Address : 277-289 Woodpark Road Smithfield NSW Australia 2164

Telephone : +61-2-8784 8555

Date Samples Received : 04-Feb-2019

Issue Date : 05-Feb-2019

**Date Analysis Commenced** 



This report supersedes any previous report(s) with this reference. Results apply to the sample(s) as submitted. This document shall not be reproduced, except in full. This Quality Control Report contains the following information:

- Laboratory Duplicate (DUP) Report; Relative Percentage Difference (RPD) and Acceptance Limits
- Method Blank (MB) and Laboratory Control Spike (LCS) Report; Recovery and Acceptance Limits
- Matrix Spike (MS) Report; Recovery and Acceptance Limits

#### Signatories

Client

This document has been electronically signed by the authorized signatories below. Electronic signing is carried out in compliance with procedures specified in 21 CFR Part 11.

Signatories Position Accreditation Category

Ankit Joshi Inorganic Chemist Sydney Inorganics, Smithfield, NSW

Page : 2 of 3 Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm

# ALS

#### General Comments

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the USEPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request.

Where moisture determination has been performed, results are reported on a dry weight basis.

Where a reported less than (<) result is higher than the LOR, this may be due to primary sample extract/digestate dilution and/or insufficient sample for analysis. Where the LOR of a reported result differs from standard LOR, this may be due to high

Key: Anonymous = Refers to samples which are not specifically part of this work order but formed part of the QC process lot

CAS Number = CAS registry number from database maintained by Chemical Abstracts Services. The Chemical Abstracts Service is a division of the American Chemical Society.

LOR = Limit of reporting

RPD = Relative Percentage Difference

# = Indicates failed QC

#### Laboratory Duplicate (DUP) Report

The quality control term Laboratory Duplicate refers to a randomly selected intralaboratory split. Laboratory duplicates provide information regarding method precision and sample heterogeneity. The permitted ranges for the Relative Percent Deviation (RPD) of Laboratory Duplicates are specified in ALS Method QWI-EN/38 and are dependent on the magnitude of results in comparison to the level of reporting: Result < 10 times LOR: No Limit: Result between 10 and 20 times LOR: 0% - 50%: Result > 20 times LOR: 0% - 20%.

Sub-Matrix: WATER					Laboratory Duplicate (DUP) Report							
Laboratory sample ID	Client sample ID	Method: Compound CAS Number		LOR	Unit	Original Result	Duplicate Result	RPD (%)	Recovery Limits (%)			
EA005P: pH by PC Titrator (QC Lot: 2168906)												
ES1903370-001	Anonymous	EA005-P: pH Value		0.01	pH Unit	7.66	7.66	0.00	0% - 20%			
ES1903346-001	Anonymous	EA005-P: pH Value		0.01	pH Unit	7.04	7.05	0.142	0% - 20%			
EA010P: Conductivity	y by PC Titrator (QC Lot: 21	68905)										
ES1903370-001	Anonymous	EA010-P: Electrical Conductivity @ 25°C		1	μS/cm	398	399	0.261	0% - 20%			
ES1903346-001	Anonymous	EA010-P: Electrical Conductivity @ 25°C		1	μS/cm	134	133	0.00	0% - 20%			

Page : 3 of 3 Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm



#### Method Blank (MB) and Laboratory Control Spike (LCS) Report

The quality control term Method / Laboratory Blank refers to an analyte free matrix to which all reagents are added in the same volumes or proportions as used in standard sample preparation. The purpose of this QC parameter is to monitor potential laboratory contamination. The quality control term Laboratory Control Spike (LCS) refers to a certified reference material, or a known interference free matrix spiked with target analytes. The purpose of this QC parameter is to monitor method precision and accuracy independent of sample matrix. Dynamic Recovery Limits are based on statistical evaluation of processed LCS.

Sub-Matrix: WATER	Method Blank (MB)	Laboratory Control Spike (LCS) Report						
	Report	Spike	Spike Recovery (%)	Recovery	ery Limits (%)			
Method: Compound	CAS Number	LOR	Unit	Result	Concentration	LCS	Low	High
EA005P: pH by PC Titrator (QCLot: 2168906)								
EA005-P: pH Value			pH Unit		4 pH Unit	100	98	102
					7 pH Unit	100	98	102
EA010P: Conductivity by PC Titrator (QCLot: 2168905)								
EA010-P: Electrical Conductivity @ 25°C		1	μS/cm	<1	2100 μS/cm	# 92.7	95	113

#### Matrix Spike (MS) Report

The quality control term Matrix Spike (MS) refers to an intralaboratory split sample spiked with a representative set of target analytes. The purpose of this QC parameter is to monitor potential matrix effects on analyte recoveries. Static Recovery Limits as per laboratory Data Quality Objectives (DQOs). Ideal recovery ranges stated may be waived in the event of sample matrix interference.

• No Matrix Spike (MS) or Matrix Spike Duplicate (MSD) Results are required to be reported.



# QA/QC Compliance Assessment to assist with Quality Review

Work Order : **ES1903377** Page : 1 of 4

Client : HARVEST SCIENTIFIC SERVICES Laboratory : Environmental Division Sydney

 Contact
 : MR MART RAMPE
 Telephone
 : +61-2-8784 8555

 Project
 : Collins Spring Farm
 Date Samples Received
 : 04-Feb-2019

 Site
 : --- Issue Date
 : 05-Feb-2019

Sampler : MART RAMPE No. of samples received : 1
Order number : 2019-2 No. of samples analysed : 1

This report is automatically generated by the ALS LIMS through interpretation of the ALS Quality Control Report and several Quality Assurance parameters measured by ALS. This automated reporting highlights any non-conformances, facilitates faster and more accurate data validation and is designed to assist internal expert and external Auditor review. Many components of this report contribute to the overall DQO assessment and reporting for guideline compliance.

Brief method summaries and references are also provided to assist in traceability.

## **Summary of Outliers**

#### **Outliers: Quality Control Samples**

This report highlights outliers flagged in the Quality Control (QC) Report.

- NO Method Blank value outliers occur.
- NO Duplicate outliers occur.
- NO Matrix Spike outliers occur.
- Laboratory Control outliers exist please see following pages for full details.
- For all regular sample matrices, NO surrogate recovery outliers occur.

#### **Outliers: Analysis Holding Time Compliance**

• NO Analysis Holding Time Outliers exist.

#### **Outliers: Frequency of Quality Control Samples**

NO Quality Control Sample Frequency Outliers exist.

Page : 2 of 4
Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm

#### **Outliers: Quality Control Samples**

Duplicates, Method Blanks, Laboratory Control Samples and Matrix Spikes

Matrix: WATER

Matrix: WATER

COLLINS GW-1

Clear Plastic Bottle - Natural (EA010-P)

Compound Group Name	Laboratory Sample ID	Client Sample ID	Analyte	CAS Number	Data	Limits	Comment
Laboratory Control Spike (LCS) Recoveries							
EA010P: Conductivity by PC Titrator	QC-MRG2-21689050		Electrical Conductivity		92.7 %	95-113%	Recovery less than lower control limit
			@ 25°C				

#### **Analysis Holding Time Compliance**

If samples are identified below as having been analysed or extracted outside of recommended holding times, this should be taken into consideration when interpreting results.

This report summarizes extraction / preparation and analysis times and compares each with ALS recommended holding times (referencing USEPA SW 846, APHA, AS and NEPM) based on the sample container provided. Dates reported represent first date of extraction or analysis and preclude subsequent dilutions and reruns. A listing of breaches (if any) is provided herein.

Holding time for leachate methods (e.g. TCLP) vary according to the analytes reported. Assessment compares the leach date with the shortest analyte holding time for the equivalent soil method. These are: organics 14 days, mercury 28 days & other metals 180 days. A recorded breach does not guarantee a breach for all non-volatile parameters.

Holding times for <u>VOC in soils</u> vary according to analytes of interest. Vinyl Chloride and Styrene holding time is 7 days; others 14 days. A recorded breach does not guarantee a breach for all VOC analytes and should be verified in case the reported breach is a false positive or Vinyl Chloride and Styrene are not key analytes of interest/concern.

Evaluation: **x** = Holding time breach; ✓ = Within holding time.

04-Mar-2019

04-Feb-2019

Method Sample Date Extraction / Preparation Analysis Container / Client Sample ID(s) Date extracted Due for extraction Evaluation Date analysed Due for analysis Evaluation EA005P: pH by PC Titrator Clear Plastic Bottle - Natural (EA005-P) 04-Feb-2019 04-Feb-2019 04-Feb-2019 COLLINS GW-1 EA010P: Conductivity by PC Titrator

04-Feb-2019

Page : 3 of 4
Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm



# **Quality Control Parameter Frequency Compliance**

The following report summarises the frequency of laboratory QC samples analysed within the analytical lot(s) in which the submitted sample(s) was(were) processed. Actual rate should be greater than or equal to the expected rate. A listing of breaches is provided in the Summary of Outliers.

Matrix: WATER

Evaluation: × = Quality Control frequency not within specification; ✓ = Quality Control frequency within specification.

Quality Control Sample Type			Count		Rate (%)		Quality Control Specification
Analytical Methods	Method	QC	Reaular	Actual	Expected	Evaluation	
Laboratory Duplicates (DUP)							
Conductivity by PC Titrator	EA010-P	2	16	12.50	10.00	✓	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Laboratory Control Samples (LCS)							
Conductivity by PC Titrator	EA010-P	1	16	6.25	5.00	✓	NEPM 2013 B3 & ALS QC Standard
pH by PC Titrator	EA005-P	2	20	10.00	10.00	✓	NEPM 2013 B3 & ALS QC Standard
Method Blanks (MB)							
Conductivity by PC Titrator	EA010-P	1	16	6.25	5.00	✓	NEPM 2013 B3 & ALS QC Standard

Page : 4 of 4 Work Order : ES1903377

Client : HARVEST SCIENTIFIC SERVICES

Project : Collins Spring Farm



#### **Brief Method Summaries**

The analytical procedures used by the Environmental Division have been developed from established internationally recognized procedures such as those published by the US EPA, APHA, AS and NEPM. In house developed procedures are employed in the absence of documented standards or by client request. The following report provides brief descriptions of the analytical procedures employed for results reported in the Certificate of Analysis. Sources from which ALS methods have been developed are provided within the Method Descriptions.

Analytical Methods	Method	Matrix	Method Descriptions
pH by PC Titrator	EA005-P	WATER	In house: Referenced to APHA 4500 H+ B. This procedure determines pH of water samples by automated ISE.
			This method is compliant with NEPM (2013) Schedule B(3)
Conductivity by PC Titrator	EA010-P	WATER	In house: Referenced to APHA 2510 B. This procedure determines conductivity by automated ISE. This method
			is compliant with NEPM (2013) Schedule B(3)